


Options:
"H" – Hardened raceways
"V" – V shape channel raceways
"F" – one outer beam countersunk
"FF" – both outer beams countersunk
"SB" – stainless steel ball bearings
"SC" – stainless steel ball cages
"SA" – stainless steel stopping pins and bolts



DDTS-12088 weights 69.4 kg/m				Hole pattern		
Article number	Installation length: L	Extension length: D	Load per pair: kg	"A"	"B"	"C"
DDTS12088.0300	300	600	640	100	-	-
DDTS12088.0350	350	700	680	50	-	50
DDTS12088.0400	400	800	720	50	-	100
DDTS12088.0450	450	900	760	50	-	150
DDTS12088.0500	500	1000	790	50	-	200
DDTS12088.0550	550	1100	810	50	-	250
DDTS12088.0600	600	1200	830	50	-	300
DDTS12088.0650	650	1300	840	50	150	-
DDTS12088.0700	700	1400	860	50	175	-
DDTS12088.0750	750	1500	880	50	200	-
DDTS12088.0800	800	1600	890	100	150	-
DDTS12088.0850	850	1700	875	100	175	-
DDTS12088.0900	900	1800	860	100	200	-
DDTS12088.0950	950	1900	845	100	225	-
DDTS12088.1000	1000	2000	830	100	250	-
DDTS12088.1050	1050	2100	810	100	275	-
DDTS12088.1100	1100	2200	800	100	300	-
DDTS12088.1150	1150	2300	790	100	325	-
DDTS12088.1200	1200	2400	780	100	350	-

**Do not dismantle the slide!**

The maximum safe working load is stated for fully extended pair of slides, mounted upright. Use all fixing holes and spread the load evenly across the inner beam.

Flat mounting: Reduce the load by 60-80%. We recommend the use of strong L brackets for under or floor mount.

Deflection is calculated up to 2% of the closed length, at or near full load capacity.

Installation tolerance:

Closed length Tolerance: DIN2768 – c

Extension Tolerance: DIN2768 - c

Installation width tolerance + 0.4 to – 0.6mm

DDTS-12088 weights 69.4 kg/m				Hole pattern		
Article number	Installation length: L	Extension length: D	Load per pair: kg	"A"	"B"	"C"
DDTS12088.1250	1250	2500	770	100	375	-
DDTS12088.1300	1300	2600	760	100	400	-
DDTS12088.1350	1350	2700	740	100	425	-
DDTS12088.1400	1400	2800	730	100	450	-
DDTS12088.1450	1450	2900	710	100	475	-
DDTS12088.1500	1500	3000	690	100	500	-
DDTS12088.1550	1550	3100	680	100	525	-
DDTS12088.1600	1600	3200	660	100	550	-
DDTS12088.1650	1650	3300	640	100	575	-
DDTS12088.1700	1700	3400	620	100	600	-
DDTS12088.1750	1750	3500	600	100	625	-
DDTS12088.1800	1800	3600	580	100	650	-
DDTS12088.1850	1850	3700	540	100	675	-
DDTS12088.1900	1900	3800	510	100	700	-
DDTS12088.1950	1950	3900	470	100	725	-
DDTS12088.2000	2000	4000	450	100	750	-
DDTS12088.2100	2100	4200	380	100	800	-
DDTS12088.2200	2200	4400	300	100	850	-

Indirect Axis (Flat) Mounting: As in the image above, reduce the load capacity by 60-80% and allow for increased deflection, or contact our engineers to request accurate FEA load analysis for OEM projects. We load rate per fully extended pair of slides on the direct axis, upright, with uniform loading across the beams, spaced 1,000mm apart. If load capacities need to be increased, or slides are fitted to extra-wide drawers, please contact us for technical advice.

Hardened Raceways Option: Via an accurate laser process, the raceways can be hardened to 58-62HRC without increasing production lead-times. This maximizes tensile strength, reduces friction coefficient, minimizes operational forces and substantially increases the life cycles. Load capacities for lengths under 700mm are marginally increased. Recommended operating speeds increase to 0.6m/s. A non-hardened Professional Range steel slide can be expected to achieve 100,000 cycles at 75% load capacity in a lifetime, following correct mounting, operational speeds, working environment and regular raceway cleaning with a re-lubrication schedule. (Download the Technical Maintenance Document for further information). Hardening raceways to achieve 58-62HRC and replicating the chromed steel ball bearings, results in substantially less wear and prolonged service life. Following the same maintenance schedule and operational conditions, lifespan can be anticipated to surpass 500,000 cycles. Our engineers can support OEM design programs with FEA analysis; however, we recommend in situ testing within the fabrication before committing to production.

Material: All steel parts.

Beams: Cold drawn carbon steel C45E+C, - EN 10277, milled raceways.

Ball cages: Zinc plated sheet steel. Laser cut profiles.

Ball bearings: C85, G100: DIN 5401 (Chromed).

End Bolts: ASTM A307.

Steel surface protection: Electrolytic alkaline zinc coating (10-12 microns). conforming to DIN EN ISO 9227 neutral salt spray testing. No white rust appearance within 250 hours. No red rust appearance within 1,100 hours

Temperature range: Steel slides –20°C to +250°C provided the necessary lubricants are applied and the beams are mounted freely to allow expansion

Lubrication: We apply and recommend lithium based EP3 grease for general applications. High & low temp grease upon request

Clean Room Requirement: The slides will be supplied unlubricated for the customer to sterilize and apply specialist grease after production

Thread pitches: As per end profile image - coarse

